

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/006786 A1

(51) International Patent Classification⁷: **A61B 17/22**

(21) International Application Number:
PCT/IB2003/002983

(22) International Filing Date: 4 July 2003 (04.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
102 31 071.8 10 July 2002 (10.07.2002) DE

(71) Applicant (for DE only): **PHILIPS INTELLECTUAL
PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).

(71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N.V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SCHWIEKER,**
Horst, Hartwig [DE/DE]; Philips Intellectual Property &

Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
SCHNABEL, Thomas [DE/DE]; Philips Intellectual
Property & Standards GmbH, Weisshausstr. 2, 52066
Aachen (DE).


(74) Agent: **VOLMER, Georg**; Philips Intellectual Property &
Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: THERAPY COMBINATION



(57) Abstract: The invention relates to a therapy combination which consists of a locating unit and a therapy unit which includes a therapy head for focusing energy in a focus, said units being movable relative to one another. In order to determine the relative position, each of said two units is provided with a sub-system of a measuring device. The position of the focus can thus be determined relative to an image produced by the locating unit.

WO 2004/006786 A1



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Therapy combination

The invention relates to a therapy combination which comprises a therapy unit which is provided with a therapy head for focusing energy in a focus, and also comprises a locating unit for locating a therapy zone within an object, the therapy unit and the locating unit being movable relative to one another.

5 A therapy combination of this kind is known from US patent 5,836,898. The therapy combination disclosed therein is formed by a locating unit in the form of an X-ray system with a C-arm mounted on a first carriage and a therapy unit in the form of a lithotripter mounted on a second carriage. The separation of the two units offers the advantage that they can both be used independently of one another.

10 However, there is the drawback that it is necessary to align the two units relative to one another when a concrement recognized in the X-ray image has to be crushed by the lithotripter. Therefore, the two units can be mechanically coupled to one another in a defined position relative to one another, the focus of the lithotripter then being situated at the point of intersection of the central ray of the X-ray system and a horizontal axis about which
15 the C-arm of the X-ray system can be pivoted. In order to enable coupling in this manner, the constructions of the two units must be adapted to one another and it is not possible, for example, to use a different C-arm X-ray apparatus.

It is an object of the present invention to construct a therapy combination of the kind set forth in such a manner that the two units can co-operate in a simple manner. This
20 object is achieved in accordance with the invention by means of a therapy combination which comprises a locating unit for locating a therapy zone within an object and also comprises a therapy unit which is provided with a therapy head for focusing energy in a focus, the therapy unit and the locating unit being movable relative to one another, there also being provided a measuring device which comprises two sub-systems and serves to determine the relative
25 position of the two sub-systems, one sub-system being attached to the locating unit while the other sub-system is attached to the therapy unit in a defined position relative to the therapy head.

In accordance with the invention the position of the two sub-systems of the measuring device relative to one another is very accurately determined. Because the two sub-

systems are rigidly connected to the two units, the position of the focus relative to the locating unit, or the alignment of the locating unit relative to the focus, is also fixed. However, the focus can then be moved to a given position of the therapy zone within an object. In accordance with the invention the constructions of the two units need not be adapted to one another. Therefore, different units can also be modified in accordance with the invention at a later stage.

It is to be noted that US patent 5,944,663 and US patent 5,368,032 already disclose a therapy combination which comprises a measuring device for determining the position in space of the therapy head. One sub-system is formed by (at least) one camera which is arranged in a fixed position in the treatment room while the other sub-system is formed by light-emitting diodes which are attached to the therapy head. Because the locating unit (an MR apparatus or a CT apparatus) is stationary and its position in space is accurately known, the therapy head can thus also be moved to a given position relative to the locating system or its position relative to the locating system can be determined.

Therapy combinations of this kind, however, have the drawback that the relative position is not determined directly but is derived from the position in space of the therapy head. In order to ensure perfect measurement, the lines of sight between the light-emitting diodes and the camera which is mounted in a fixed position in space may not be interrupted, for example, by the staff carrying out the treatment.

This requirement would be very difficult to satisfy if the locating unit were not stationary either and if its position would also have to be determined by means of the camera (or additional cameras). However, when the therapy combination in accordance with the invention is used, the locating unit and the therapy unit are situated very close to one another so that it is rather unlikely that the measurement of the relative position will be influenced by the attendant staff. It is a further advantage that the distance between the two systems in accordance with the invention is comparatively small. Therefore, the absolute measuring error will also be comparatively small.

The relative position determined for the two sub-systems (or for the focus and the locating unit) suffices in principle to move the two units relative to one another to an exactly defined position and to position the object relative to the focus also in such a manner that the zone to be treated is situated in the focus. The user would not have to know this relative position if this alignment or positioning were to take place automatically by means of an appropriate drive. However, this would be a very intricate operation. Therefore, claim 2 discloses a solution which is far simpler. The visualization of the position of the focus in an

image as disclosed therein allows the attendant staff to align the two units relative to one another and to position the object to be treated. The position of the focus can then be marked already before an image has been formed by means of the locating unit, because the position of this image is predetermined on the display unit (for example, a monitor), so that from the representation of the mark on the monitor it is already evident where it is situated, for example, relative to the center of the image.

Claim 3 discloses a preferred embodiment of the measuring device. The position and the alignment of the two sub-systems relative to one another can be determined exactly from the times of flight of the ultrasound signals from each of the (at least) three ultrasound transmitters to each of the (at least) three ultrasound receivers when the ultrasound speed is known.

An optical measuring device, in which one or more cameras would have to be attached to one unit and, for example, light-emitting diodes would have to be attached to the other unit, could also be used instead of a measuring device based on ultrasound. In that case a transmission system (light-emitting diodes) would be provided on one unit while a receiving system (camera) would be provided on the other unit. Transmitter and receiver, however, could also be attached to one unit if the other unit were provided with reflecting structures.

Claim 4 discloses a preferred embodiment of the invention. It enables the use of the two units and the room in which they are present for other purposes. However, it is not necessary to mount each of the two units on a respective carriage; one of the two units may also be installed in a fixed position.

Instead of the embodiment disclosed in claim 5, use could also be made of a locating system in the form of an ultrasound imaging system; however, a locating system based on X-rays offers the advantage, for example, when used for lithotripsy, that practically all concrements are reproduced in an X-ray image, whereas many concrements will not become visible in an ultrasound image.

The embodiment disclosed in claim 6 enables simple variation of the radiation direction by means of the C-arm, for example, for three-dimensional localization of a concrement. The further embodiment disclosed in claim 7 then enables measurement of a change of the position of the X-ray converter relative to the X-ray source (for example, due to deformation of the C-arm) by means of a third system so as to take this change into account for the determination of the relative position of the locating unit and the therapy head.

Claim 8 describes the use of a measuring device in a therapy combination as claimed in claim 1.

Claim 9 describes a preferred embodiment of a therapy system provided with a therapy combination in accordance with the invention and with a patient table. Granted, it
5 would also be possible to use a table with a stationary table top, but in that case the therapy head would have to be displaced accordingly and the locating unit would have to follow this displacement at least partly.

The invention will be described in detail hereinafter on the basis of an embodiment as shown in the drawings. Therein:

10 Fig. 1 is a perspective view of a therapy system with the therapy combination in accordance with the invention, and

Fig. 2 is a block diagram of a part of such a therapy combination.

The reference numeral 1 in Fig. 1 designates a locating unit while the reference numeral 2 designates a therapy unit and the reference numeral 3 designates a
15 patient table.

The locating unit 1 is intended to determine the therapy zone to be treated within a patient who is arranged on the patient table 3 and to position this zone in such a manner that it is situated in the focus of a therapy head of the therapy unit. The locating unit includes an X-ray image converter 101 and an X-ray source 102 which are attached to the
20 ends of a C-arm 103 and are aligned relative to one another. The C-arm 103, and hence the X-ray image converter 101 and the X-ray source 102, can be pivoted in the plane defined thereby and is journaled so as to be pivotable on a horizontal supporting arm 104. The supporting arm 104 is mounted on a carriage 105 so that its height is adjustable; this carriage also accommodates, arranged in a housing 106, the sub-systems required for the power
25 supply of the components 101 and 102 and for the processing of the image signals delivered by the image converter.

Instead of an X-ray locating unit, an ultrasound imaging system could also be used in principle. For lithotripsy applications, however, an X-ray system offers the advantage that it is capable of imaging concrements of practically any type, whereas an ultrasound
30 locating system cannot image given types of concrements. For lithotripsy purposes, therefore, ultrasound locating systems are normally used only as additional systems.

The therapy unit 2 includes a carriage 201 which supports a therapy head 203 which is displaceable and pivotable on an arc-like segment 202. The therapy head 203 serves to generate shockwaves, notably for the crushing of concrements (for example, renal calculi)

and may include in known manner a rotation ellipsoid in which an electric discharge takes place via a spark gap, which discharge is fed by a generator 204 which is preferably also arranged on the carriage 201 of the therapy unit 2. The rotation ellipsoid (not shown) communicates with a liquid reservoir (not shown either) which contains a suitable liquid
5 acoustic medium, for example, water, and is sealed from the environment by means of a flexible coupling diaphragm 205. The energy of the shock wave generated is concentrated in one point (the focus) by the rotation ellipsoid, the position of said point relative to the shock wave head 205 being known.

The patient table 3 comprises a table top 301 which serves to accommodate a
10 patient and is displaceable in a horizontal plane. The table top 301, moreover, can be adjusted in respect of height by means of a motor, thus enabling movement of the table top in three mutually perpendicular directions. The table top is provided with a cut-out 302 wherethrough the therapy head 203 can act on a patient arranged on the table top.

In order to enable alignment of the focus of the therapy head 203 relative to
15 the therapy zone in the form of a concrement inside the patient, the concrement must be located by means of the locating unit 1, that is, by way of an X-ray exposure or X-ray fluoroscopy, and its position in the X-ray image must be related to the position of the focus of the therapy head. To this end, there is provided a measuring device whereby the relative position is determined of the locating unit 1 and the therapy unit 2. The measuring device
20 includes two sub-systems, one of which is rigidly connected to the X-ray image converter 101 whereas the other sub-system is rigidly connected to the therapy head 203.

The sub-system connected to the X-ray image converter 101 includes a plate
107 on which (at least) three ultrasound microphones 108 are arranged in such a manner that they define a triangle (that is, not a line). The sub-system connected to the therapy head 203
25 includes a plate 207 on which (at least) three ultrasound transmitters 208 are arranged in such a manner that they too do not define a line but a polygon (triangle).

Fig. 2 is a block diagram of the measuring device and some further
components of the therapy combination. The ultrasound transmitters 208 are connected to a generator 209 which is controlled by an arithmetic and control unit 4 in such a manner that
30 the three ultrasound transmitters successively transmit pulse-shaped ultrasound signals. The ultrasound signals are received by the three ultrasound receivers 108, are amplified by amplifiers 109 and applied to an evaluation unit 111 which, together with the generator 209, forms part of an ultrasound measuring device which measures the times of flight of the

ultrasound signal from the respective active ultrasound transmitter to each of the three ultrasound receivers and stores these times, if desired.

When the ultrasound speed is known, the distances between the active ultrasound transmitter and each of the three receivers can be calculated from the times of flight measured (by means of the arithmetic and control unit 4). The position of the active transmitter relative to the three receivers is thus defined. For the positions of the other two ultrasound transmitters, however, various possibilities still exist and the relation in space between the two sub-systems 107, 108 and 207, 208 is unambiguously defined only after the times of flight from all ultrasound transmitters to all ultrasound receivers have been measured and the corresponding distances have been calculated therefrom. This also defines the position and the orientation of the X-ray system 101, 102 in relation to the therapy head 203 or, because of the known position of the focus relative to the therapy head, in relation to the focus.

The execution of a treatment by means of the therapy system shown in Fig. 1 will now be described in detail.

First the patient to be treated is arranged on the table top 3 in such a manner that the zone in which the concrement is expected to be present is situated at the area of the cut-out 302. The therapy unit 2 is then moved towards the patient until the diaphragm 205 of the therapy head 203 contacts the patient. Subsequently, the locating system 1 is moved closer; the X-ray source 102 and the image converter 101 should then be aligned relative to one another in such a manner that a vertical central ray is obtained (being the connecting line between the focal spot of the X-ray source 102 and the center of the image converter 101). Subsequently, the relative position of the two units 1 and 2 is determined and hence the position of the focus relative to the central ray. The position of the focus as calculated by the arithmetic and control unit 4 is reproduced by way of a mark F_2 on a monitor 5 on which subsequently the X-ray image is also displayed. The position of the central ray is defined by the center M of the image which is fixed already before the formation of the X-ray image. The mark F_2 for the focus is then displayed in the position in the image in which the focus would appear in an X-ray image if it were to consist of a material-absorbing X-rays and if it were projected onto the image converter 101 by X-rays.

The carriage 105 of the locating unit 1 is then displaced until the mark F_2 coincides with the center M of the image, that is, until the focus is situated on the (vertical) central ray.

Subsequently, an X-ray image is formed by means of an X-ray exposure or by X-ray fluoroscopy, said image being displayed on the monitor M. The therapist then defines in this first X-ray image, for example, by means of cross-hairs which can be moved by way of a suitable input unit, the position of the concrement to be crushed, said position usually not
5 being coincident with the center M. Subsequently, controlled either manually or automatically by the position of the cross-hairs in relation to the center M of the image, the patient table 301 is displaced horizontally until the concrement to be crushed appears at the same point of the X-ray image as the focus. Generally speaking, the focus and the concrement still do not coincide in space in all cases. However, they are situated on the
10 central ray, that is, one over the other in the vertical direction.

Subsequently, the X-rays are switched off and the C-arm 103 is pivoted in such a manner that the central ray extends, for example, at a defined angle of, for example, 30° relative to the vertical. The position of the focus is determined again and the mark F₂ is reproduced in this image. It will usually no longer be situated at the center of the image.
15 Generally speaking, the concrement will usually no longer be imaged at the center M either in the X-ray image formed again in this position of the C-arm. However, because the focus and the concrement have already been positioned on a vertical line, it is now only necessary to lift or lower the table top 301 until the focus and the concrement coincide in this image. Subsequently, shock waves for crushing the concrement can be generated by means of the
20 therapy head, the concrement then being situated exactly in the focus.

In practice the C-arm is not rigid, but may become deformed under the influence of the weight of the components 101 and 102 (and its own weight). This deformation can be determined by means of a monitoring device, comprising a further ultrasound transmitter 110 (only one is shown in Fig. 1), by measuring also the times of flight
25 from these ultrasound transmitters to the ultrasound receivers 108 in each of the two irradiation directions, by determining therefrom the position and the alignment of the two components 101 and 102, and by calculating therefrom the deformation that can then be used to correct the positioning.

An advantage of the invention resides in the fact that the constructions of the
30 locating unit 1 and the therapy unit need not be adapted to one another, as opposed to, for example, the therapy combination mentioned in the preamble. This makes it possible to modify already existing units in the sense of the invention. In that case usually a (one time) calibration measurement is necessary to determine, using suitable phantom bodies, the position and the orientation of the central ray in relation to the sub-system 107, 108 of the

measuring device, connected to the locating unit 1, and also the position of the focus in relation to the sub-system 207, 208 which is connected to the therapy head 203.

The therapy head can also generate the shockwaves in a manner other than by means of a discharge of a spark gap. The therapy head may also be active in a manner other
5 than by means of shockwaves, for example, as described in the previously cited US patent 5,944,663 and US patent 5,368,032.

CLAIMS:

1. A therapy combination which comprises a locating unit (1) for locating a therapy zone within an object and also comprises a therapy unit (2) which is provided with a therapy head (203) for focusing energy in a focus (F_2), the therapy unit (2) and the locating unit (1) being movable relative to one another, there also being provided a measuring device
5 which comprises two sub-systems and serves to determine the relative position of the two sub-systems, one sub-system (107, 108) being attached to the locating unit (1) while the other sub-system (207, 208) is attached to the therapy unit (2) in a defined position relative to the therapy head (203).
- 10 2. A therapy combination as claimed in claim 1, which comprises a display unit (5) for the display of images formed by means of the locating unit (1), and also comprises means (100, 4) for determining the position of the focus in an image formed by the locating unit from the determined relative position of the sub-systems, and also means (4) for generating a mark (F_2) characterizing the position in the image.
- 15 3. A therapy combination as claimed in claim 1, in which one sub-system comprises an ultrasound transmission unit with at least three ultrasound transmitters (208) which are situated at a distance from one another whereas the other sub-system includes an ultrasound receiving unit with at least three ultrasound receivers (108) which are situated at a
20 distance from one another, there being provided means (111) for measuring the times of flight of the ultrasound signals from the ultrasound transmitters to the ultrasound receivers and means (4, 111) for determining the position of the ultrasound receiving unit relative to the ultrasound transmission unit.
- 25 4. A therapy combination as claimed in claim 1, in which the therapy unit (2) and the locating unit (1) are displaceable on a respective carriage (01, 105).
5. A therapy combination as claimed in claim 1, which comprises a locating system provided with an X-ray source (102) and an X-ray image converter (101).

6. A therapy combination as claimed in claim 5, in which the X-ray source (102) and the X-ray image converter (101) are attached to the ends of a C-arm (103), the associated sub-system (107, 108) of the measuring device being attached to the C-arm or to one of the components attached thereto, preferably to the X-ray image converter (101).

7. A therapy combination as claimed in claim 6, in which the sub-system (108) associated with the locating unit (1) is attached to the X-ray image converter or to the X-ray source, and a third sub-system (110) which co-operates therewith is attached to the X-ray source, or to the X-ray image converter, in order to monitor the relative position of the X-ray image converter and the X-ray source.

8. The use of a measuring device (4, 110) with two sub-systems (108, 208) which are to be attached to the units of a therapy combination (1, 2) as claimed in claim 1 in order to determine the relative position of the two sub-systems or of the units.

9. A therapy system which comprises a therapy combination as claimed in claim 1 and a patient table (3) whose table top can be displaced in three mutually perpendicular directions.

1/2




FIG. 1

2/2




FIG. 2

INTERNATIONAL SEARCH REPORT

Inter _ cation No

PCT/IB 03/02983

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B17/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-----------------------|
| X | DE 90 17 443 U (DORNIER MEDIZINTECHNIK GMBH) 7 March 1991 (1991-03-07) the whole document | 1-7 |
| Y | --- | 8 |
| Y | US 5 836 898 A (SCHWIEKER HORST) 17 November 1998 (1998-11-17) cited in the application column 3, line 50 -column 5, line 40; figures 1-5 column 4, line 56 - line 59 | 8 |
| A | --- | 1,2,5 |
| A | FR 2 682 868 A (SIEMENS AG) 30 April 1993 (1993-04-30) page 19, line 13 -page 20, line 13; figures 1,2 --- -/-- | 1,2 |

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

13 November 2003

Date of mailing of the international search report

26/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Ducreau, F

INTERNATIONAL SEARCH REPORT

Application No
PCT/IB 03/02983

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-----------------------|
| A | DE 195 12 956 A (STORZ MEDICAL AG) 17 October 1996 (1996-10-17) column 3, line 14 - line 32; figure 2 ----- | 1 |
| P,A | DE 102 06 193 C (SIEMENS AG) 3 July 2003 (2003-07-03) abstract; figure 1 ----- | 1,2,5,6 |

INTERNATIONAL SEARCH REPORT

Int. Application No.

PCT/IB 03/02983

| Patent document cited in search report | | Publication date | Patent family member(s) | Publication date |
|---|---|---------------------|----------------------------|---------------------|
| DE 9017443 | U | 07-03-1991 | DE 9017443 U1 | 07-03-1991 |
| US 5836898 | A | 17-11-1998 | DE 4443495 A1 | 20-06-1996 |
| | | | DE 59505117 D1 | 25-03-1999 |
| | | | EP 0715831 A1 | 12-06-1996 |
| | | | JP 8215203 A | 27-08-1996 |
| FR 2682868 | A | 30-04-1993 | DE 4135177 A1 | 29-04-1993 |
| | | | DE 4143540 C2 | 08-08-1996 |
| | | | FR 2682868 A1 | 30-04-1993 |
| | | | JP 5237131 A | 17-09-1993 |
| | | | US 5285772 A | 15-02-1994 |
| DE 19512956 | A | 17-10-1996 | DE 19512956 A1 | 17-10-1996 |
| DE 10206193 | C | 03-07-2003 | DE 10206193 C1 | 03-07-2003 |

This Page Blank (uspto)